

Tel: 01506 412791

Email: sales@esl-services.co.uk

Web: www.esl-services.co.uk

LG2004 T-Lift



Stairlift with tracks and platforms.

The LG2004 T-Lift is suitable for any wheelchair model as it is equipped with different types of ramps.

Thanks to its intuitive LED display, operators can manoeuvre the stairlift effortlessly, viewing the recommended movements for safe ascent and descent. The lift ensures that the user stays upright and comfortable due to its ability to tilt 55 degrees, as well as having an exceptional load capacity of up to 300kg.

The T-Lift offers a customised mobility experience for every user, overcoming architectural barriers with comfort and safety.

Applications

- ◆ Designed to overcome architectural barriers with comfort and safety
- ◆ Suitable for L-shaped and U-shaped landings.

Why buy the LG2004 T-Lift?

- ◆ Suitable for various types of wheelchairs thanks to the different ramps
- ◆ Intuitive driving thanks to the innovative
- ◆ LED display
- ◆ Large load capacity up to 300kg
- ◆ Multi position backrest and adjustable headrest for optimal comfort
- ◆ 3D wheelchair anchor support

About us

ESL Services provide the most comprehensive range of evacuation chairs and stairclimbers to improve safety when getting people in and out of buildings. Important - people have different needs and therefore require different choices.




Tel: 01506 412791


Email: sales@esl-services.co.uk

Web: www.esl-services.co.uk


Specifications





Short Platform



Low Platform



High Platform

Overall Weight (kg)	77	79	89
Maximum body weight (kg)	70	70	70
Weight of accessories (kg)	7	9	19
Minimum overall dimensions (cm)	66 x 97 x 110	66 x 106 x 110	69 x 106 x 110
Maximum overall dimensions (cm)	83 x 97 x 150	83 x 106 x 150	86 x 106 x 150
Maximum step height (cm)	21	21	21
Power Battery (V)	2 - 12v - 12Ah	2 - 12v - 12Ah	2 - 12v - 12Ah
Motor Power (w)	500	500	500
Battery charger power consumption (w)	80	80	80
Battery charger power supply (v)	100 - 240	100 - 240	100 - 240
Maximum transportable weight (kg)	350	350	350
Autonomy (steps)	850 (with 150 kg load) - 520 (with 350 kg load)		
Autonomy with reserve indicator (steps)	60	60	60
Minimum Stair width (cm)	64	64	64
Maximum tilt (degrees)	45	45	45
Temperature of use	0 - 40	0 - 40	0 - 40
Storage temperature with packaging (dry environment)	-10 - -50	-10 - -50	-10 - -50
Maximum speed	13 steps per minute		
Packaging Dimensions	60 x 115 x 40	60 x 115 x 40	60 x 115 x 40
Warranty	2 Years		
Manufacturer	Antano		
Minimum Manoeuvring space on a L-Shaped Landing (cm)	 97 x 97	115 x 115	115 x 115
Minimum Manoeuvring space on a U-Shaped Landing (cm)	 97 x 194	115 x 230	115 x 230